




K 250 STATIC



LW-K 250



GENERAL FEATURES

- Wall fixing or stationary use configuration
- Sturdy stainless steel casing
- Easy maintenance by simply removing the casing
- Low-pressure detergent suction
- Pressure gauge
- LWK-250 Comet pump with hot water seals
- 4-pole motor (1400 rpm) well oversized and protected with paint
- Built-in professional unloader valve
- **TotalStop**
- Self-priming pumps with **EASY-START** device on single-phase models
- Rotary switch
- Motor thermal protection



CARATTERISTICHE GENERALI

- *Configurazione per fissaggio a muro o per utilizzo stazionario*
- *Robuste carenature in acciaio inossidabile*
- *Facile manutenzione con la semplice rimozione della carenatura*
- *Aspirazione detergente in bassa pressione*
- *Manometro di pressione*
- *Pompa LWK-250 Comet con guarnizioni acqua calda.*
- *Motore a 4 poli (1400 giri/min) ampiamente sovradimensionato e protetto da verniciatura*
- *Valvola di regolazione professionale integrata*
- **TotalStop**
- *Pompe autoadescenti con dispositivo **EASY-START** per modello monofase*
- *Interruttore rotativo*
- *Protezione termica motore*
- *Usa professionale*

ON THE WALL › A PARETE

Dual use
Doppio uso

ON THE FLOOR › A TERRA



CODE CODICE	MODELS MODELLI	PUMP POMPA													
			Ph	V	Hz	bar	MPa	bar	MPa	l/h	HP	kW	kW	kg	(L x W x H) cm
9057 2001	K 250 Static 10/150 M	LW-K 250	1	230	50	150	15	135	13,5	600	3,0	2,2	2,9	40	55 x 35 x 35
9057 2003	K 250 Static 12/130 M	LW-K 250	1	230	50	130	13	120	12	720	3,0	2,2	2,9	40	55 x 35 x 35
9057 2002	K 250 Static 15/170 T	LW-K 250	3	400	50	170	17	160	16	900	5,5	4,0	5,0	40	55 x 35 x 35



STANDARD ACCESSORIES › DOTAZIONE STANDARD

	<i>GH 301 gun with swivel</i> Pistola GH 301 con swivel		Fan shape nozzle, 1/4" MEG connection <i>Ugello con getto a lama attacco 1/4" MEG</i>
	Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>		10 m rubber delivery hose kit with quick coupler M22x1,5 <i>Kit tubo gomma mandata 10m, con attacco rapido M22x1,5</i>
		Ejector kit <i>Kit eiettore</i>	