

Maximum Working Pressures to:	500 psi 3450 kPa 35 bar
Rated Static Burst to:	1000 psi 6895 kPa 69 bar
Flow Range to:	HMK04 133 lpm HMK24 227 lpm



HMK04 Single Filter Head

Port Size	Bypass Rating	Gauge/Indicator Port	Gauge/Indicator Options	Part Number
3/4" BSPP	25 psi / 172 kPa / 1.72 bar	Left side	None	P766295
3/4" NPT	25 psi / 172 kPa / 1.72 bar	Left side	None	P169310
SAE-12 O-Ring	25 psi / 172 kPa / 1.72 bar	Left side	None	P166387
SAE-12 O-Ring	No Bypass	Left side	None	P169320
1" BSPP	25 psi / 172 kPa / 1.72 bar	Left side	Electric	P766296
1" NPT	25 psi / 172 kPa / 1.72 bar	Both sides	Electric	P166086
SAE-16 O-Ring	25 psi / 172 kPa / 1.72 bar	Both sides	Electric	P166088
SAE-16 O-Ring	No Bypass	Both sides	Electric	P166664

HMK24 Dual Filter Head Assemblies

Port Size	Bypass Rating	Gauge/Indicator Port	Gauge/Indicator Options	Part Number
SAE-20 O-Ring	No Bypass	None	Electric	P179609
1 1/4" SAE 4 Bolt Flange code 61	50 psi / 345 kPa / 3.45 bar	None	Electric	P179582

HMK04, 24 Spin-on Filters

Filter Media	Micron Rating	Length (mm)	Length (in)	Part Number
Synteq	<4um @ B1000	240	9.4	*P165185
Synteq	6um @ B1000	152	6	P165354
Synteq	6um @ B1000	240	9.4	P165332
Synteq	11um @ B1000	152	6	P164375
Synteq	11um @ B1000 500 psi collapse	152	6	P163542
Synteq	11um @ B1000	240	9.4	P164378
Synteq	11um @ B1000 350 psi working pressure	295 O.D. 121	11.6	P179343

Continued on page 14...

HMK04, 24 Spin-on Filters (Continued)

Filter Media	Micron Rating	Length (mm)	Length (in)	Part Number
Synteq	23um @ β 1000	113	4.5	P169078
Synteq	23um @ β 1000	152	6	P164381
Synteq	23um @ β 1000	240	9.4	P164384
Synteq	23um @ β 1000 500 psi collapse	240	9.4	P163567
Synteq	50um @ β 1000	118	4.68	P765352
Synteq	50um @ β 1000	152	6	P165335
Synteq	50um @ β 1000	240	9.4	P165338
Wire mesh	150um	240	9.4	P573301
SAP	Water Absorb	240	9.4	P560584

Note: Seal material is Buna-N[®] unless marked *
* epoxy potting and Viton[®] seals

HMK05, 25 Max Flow: HMK 05 189 lpm HMK25 379 lpm

Maximum Working Pressures to:
350 psi
2415 kPa
25.4 bar

Rated Static Burst to:
800 psi
5520 kPa
55.2 bar

Flow Range to:
HMK05 189 lpm
HMK25 379 lpm



HMK05 Single Head Assemblies

Port Size	Bypass Rating	Gauge/Indicator Port	Gauge/Indicator Options	Part Number
1 1/4" BSPP	25 psi / 172 kPa / 1.72 bar	Left side	Electric	P173448
1 1/4" NPT	25 psi / 172 kPa / 1.72 bar	Both sides	Electric	P167294
SAE-20 O-Ring	25 psi / 172 kPa / 1.72 bar	Both sides	Electric	P165973
SAE-20 O-Ring	50 psi / 345 kPa / 3.45 bar	Left side	Electric	P561885
SAE-20 O-Ring	No Bypass	Both sides	Electric	P166663

HMK25 Dual Head Assembly

Port Size	Bypass Rating	Gauge/Indicator Port	Gauge/Indicator Options	Part Number
1 1/2" SAE 4 Bolt Flange Code 61	25 psi / 172 kPa / 1.72 bar	Both	Visual/Electric	P167296

HMK05, 25 Spin-on Filters

Filter Media	Micron Rating	Length (mm)	Length (in)	Part Number
Synteq	<4um @ β 1000	361	14.2	*P564468
Synteq	6um @ β 1000	294	11.6	*P171274
Synteq	6um @ β 1000	294	11.6	P165675
Synteq	6um @ β 1000	361	14.2	P179763
Synteq	11um @ β 1000	294	11.6	*P171275
Synteq	11um @ β 1000	294	11.6	P165659
Synteq	11um @ β 1000	361	14.2	P170949
Synteq	23um @ β 1000	294	11.6	P165569
Synteq	23um @ β 1000	361	14.2	P173789
Synteq	50um @ β 1000	294	11.6	P165672
Wire mesh	150um	294	11.6	P173943
SAP	Water Absorb	294	11.6	P179075

Note: Seal material is Buna-N® unless marked *
* epoxy potting and Viton® seals

Indicators

Indicator Options	Setting	Description	Series	Part Number
Visual	25 psi / 172 kPa / 1.72 bar	Slide Heavy Duty	All HMK	P165965
Visual	25 psi / 172 kPa / 1.72 bar	Slide	HMK04, 05/25	P162696
Visual	50 psi / 345 kPa / 3.45 bar	Slide	HMK04, 05/25	P167580
Visual		Blanking plate	HMK04, 05/25	P165984
Visual	18 psi / 117 kPa / 1.17 bar	Pop-up	All HMK	P575334
Visual	40 psi / 275 kPa / 2.75 bar	Pop-up	All HMK	P575335
Electrical	25 psi / 172 kPa / 1.72 bar	DC single post	All HMK	P162400
Electrical	25 psi / 172 kPa / 1.72 bar	AC/DC open/closed	All HMK	P173944
Electrical	50 psi / 345 kPa / 3.45 bar	AC/DC open/closed	All HMK	P174396
Electrical	50 psi / 345 kPa / 3.45 bar	AC/DC open/closed	Microprocessor Compatible	P575549
Vis/elec 3 wire comb	35 psi / 241 kPa / 2.41 bar	AC/DC open/closed	W041	P572349

